

NAME

pod2html - convert .pod files to .html files

SYNOPSIS

```
pod2html --help --htmlroot=<name> --infile=<name> --outfile=<name>
--podpath=<name>:...:<name> --podroot=<name>
--libpods=<name>:...:<name> --recurse --norecurse --verbose
--index --noindex --title=<name>
```

DESCRIPTION

Converts files from pod format (see *perlpod*) to HTML format.

ARGUMENTS

pod2html takes the following arguments:

help

```
--help
```

Displays the usage message.

htmlroot

```
--htmlroot=name
```

Sets the base URL for the HTML files. When cross-references are made, the HTML root is prepended to the URL.

infile

```
--infile=name
```

Specify the pod file to convert. Input is taken from STDIN if no infile is specified.

outfile

```
--outfile=name
```

Specify the HTML file to create. Output goes to STDOUT if no outfile is specified.

podroot

```
--podroot=name
```

Specify the base directory for finding library pods.

podpath

```
--podpath=name:...:name
```

Specify which subdirectories of the podroot contain pod files whose HTML converted forms can be linked-to in cross-references.

libpods

```
--libpods=name:...:name
```

List of page names (eg, "perlfunc") which contain linkable `items`.

netscape

```
--netscape
```

Use Netscape HTML directives when applicable.

nonetscape

`--nonetscape`

Do not use Netscape HTML directives (default).

index

`--index`

Generate an index at the top of the HTML file (default behaviour).

noindex

`--noindex`

Do not generate an index at the top of the HTML file.

recurse

`--recurse`

Recurse into subdirectories specified in podpath (default behaviour).

norecurse

`--norecurse`

Do not recurse into subdirectories specified in podpath.

title

`--title=title`

Specify the title of the resulting HTML file.

verbose

`--verbose`

Display progress messages.

AUTHOR

Tom Christiansen, <tchrist@perl.com>.

BUGS

See *Pod::Html* for a list of known bugs in the translator.

SEE ALSO

perlpod, *Pod::Html*

COPYRIGHT

This program is distributed under the Artistic License.